



SN Drop-Down Door Seal

Product # 105093L

Length 36 1/4 in*

Handing Position / Opening Side Left-Hand Opening

DESCRIPTION

SN for sliding doors
 No door locking necessary due to zero-force release
 Seal height: 7-16 mm
 Floor guidance set SN - varieties short (standard) and long (optional) - for soil air 7-10 / 10-13 / 13-16 mm
 Release force only 1 N/m
 Triggered by floor guide with parallel lowering
 Compact, space-saving solution with integrated floor guide groove
 Automatic compensation for sloping floors
 With optimal sealing, sound insulation value up to 44 dB (at 7 mm ground clearance)
 High-quality silicone lip
 Closing edge can be shortened to the next shorter storage length, can be shortened to 45 mm on the release side (see installation instructions, point "3/4 extra")
 The seal can be easily removed by loosening the bracket
 7-year guarantee

ADVANTAGES AND BENEFITS

Smoke-proof Sound-insulating 7-year guarantee

TECHNICAL SPECIFICATIONS

Product #	105093L
Color/Finish	Aluminum
Door Type	Wood, Metal, PVC
Screw	Included
Height	1 3/16 in*
Width	7/8 in*
Material	Aluminum
Brand	Planet
Usage	Sliding Door

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

For sliding doors For wood doors Can also be used with metal and PVC doors

PRODUCT PHOTOS

