



146BC Bypass Door Hardware Kit - with Track

Product # 14672BC

Overall Length 72 in

Door Width Max. 36 in

DESCRIPTION

Allows doors to move easily

The Onward 146BC Bypass Door Hardware Kit with Track includes everything you need to install bypass sliding doors in your home. The kit includes a sliding door track, adjustable floor guide, four dial-adjust door hangers, two brass-plated finger pulls and fasteners. Install your doors quickly and easily using a drill and screwdriver: no other tools are required. The included parts allow you to make adjustments for different door thicknesses. The track is jump-proof and made of corrosion-resistant galvanized steel, ideal for humid environments. The kit comes in various sizes designed for use with common door widths. Simply choose a kit based on the width of your doors. This kit is also ideal if you need replacement parts to repair an older bypass door.

Use the Onward Bypass Door Hardware Kit to install bypass doors in your bathroom, closet, wardrobe, bedroom, or any other interior space. Fashionable and practical, bypass doors are also ideal for tight spaces that can't accommodate a regular hinged door.

ADVANTAGES AND BENEFITS

Dial-adjustable door hangers simplify door adjustment and alignment. V-shaped track is jump-proof and constructed of corrosion-resistant galvanized steel.



TECHNICAL SPECIFICATIONS

Product # 14672BC Door Material Wood Door Movement Straight Sliding Track Mounting Ceiling Mount Load Capacity Max. 60 lb Door Position Inside Frame Door Thickness 3/4 to 1 3/8 in Roller Type Axle (Bushing) Roller Position Upper Application Closet and Walk-In Closet, Storage Brand Onward Screw/Nail Included Yes Packaging Format Box Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors 2 Door Height 36 to 98 in		
Door Movement Straight Sliding Ceiling Mount Load Capacity Max. 60 lb Door Position Inside Frame Door Thickness 3/4 to 1 3/8 in Roller Type Axle (Bushing) Roller Position Upper Application Closet and Walk-In Closet, Storage Brand Onward Screw/Nail Included Yes Packaging Format Box Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors Zinc Sinc Sinc Sinc Sinc Sinc Sinc Sinc S	Product #	14672BC
Track Mounting Ceiling Mount Load Capacity Max. 60 lb Door Position Inside Frame Door Thickness 3/4 to 1 3/8 in Roller Type Axle (Bushing) Roller Position Upper Application Closet and Walk-In Closet, Storage Brand Onward Screw/Nail Included Yes Packaging Format Box Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Number of Doors 2 2	Door Material	Wood
Load CapacityMax. 60 lbDoor PositionInside FrameDoor Thickness3/4 to 1 3/8 inRoller TypeAxle (Bushing)Roller PositionUpperApplicationCloset and Walk-In Closet, StorageBrandOnwardScrew/Nail IncludedYesPackaging FormatBoxManufacturing MaterialSteelFinishZincSoft-ClosingNoProduct typeBypass Top RollerGroove Needed for Guiding SystemNoOverall Width1 inDoor InstallationTop HungNumber of Doors2	Door Movement	Straight Sliding
Door PositionInside FrameDoor Thickness3/4 to 1 3/8 inRoller TypeAxle (Bushing)Roller PositionUpperApplicationCloset and Walk-In Closet, StorageBrandOnwardScrew/Nail IncludedYesPackaging FormatBoxManufacturing MaterialSteelFinishZincSoft-ClosingNoProduct typeBypass Top RollerGroove Needed for Guiding SystemNoOverall Width1 inDoor InstallationTop HungNumber of Doors2	Track Mounting	Ceiling Mount
Door Thickness 3/4 to 1 3/8 in Roller Type Axle (Bushing) Roller Position Upper Application Closet and Walk-In Closet, Storage Brand Onward Screw/Nail Included Yes Packaging Format Box Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors 2	Load Capacity	Max. 60 lb
Roller Type Axle (Bushing) Roller Position Upper Application Closet and Walk-In Closet, Storage Brand Onward Screw/Nail Included Yes Packaging Format Box Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors Axle (Bushing) Axle (Bushin	Door Position	Inside Frame
Roller Position Upper Application Closet and Walk-In Closet, Storage Brand Onward Screw/Nail Included Yes Packaging Format Box Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors 2	Door Thickness	3/4 to 1 3/8 in
Application Closet and Walk-In Closet, Storage Brand Onward Screw/Nail Included Yes Packaging Format Box Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors 2	Roller Type	Axle (Bushing)
Brand Onward Screw/Nail Included Yes Packaging Format Box Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors 2	Roller Position	Upper
Screw/Nail IncludedYesPackaging FormatBoxManufacturing MaterialSteelFinishZincSoft-ClosingNoProduct typeBypass Top RollerGroove Needed for Guiding SystemNoOverall Width1 inDoor InstallationTop HungNumber of Doors2	Application	Closet and Walk-In Closet, Storage
Packaging Format Manufacturing Material Steel Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors 2	Brand	Onward
Manufacturing MaterialSteelFinishZincSoft-ClosingNoProduct typeBypass Top RollerGroove Needed for Guiding SystemNoOverall Width1 inDoor InstallationTop HungNumber of Doors2	Screw/Nail Included	Yes
Finish Zinc Soft-Closing No Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors 2	Packaging Format	Box
Soft-ClosingNoProduct typeBypass Top RollerGroove Needed for Guiding SystemNoOverall Width1 inDoor InstallationTop HungNumber of Doors2	Manufacturing Material	Steel
Product type Bypass Top Roller Groove Needed for Guiding System No Overall Width 1 in Door Installation Top Hung Number of Doors 2	Finish	Zinc
Groove Needed for Guiding System Overall Width 1 in Top Hung Number of Doors 2	Soft-Closing	No
Overall Width 1 in Door Installation Top Hung Number of Doors 2	Product type	Bypass Top Roller
Door Installation Top Hung Number of Doors 2	Groove Needed for Guiding System	No
Number of Doors 2	Overall Width	1 in
	Door Installation	Top Hung
Door Height 36 to 98 in	Number of Doors	2
	Door Height	36 to 98 in

INCLUDED PRODUCT(S)

Each kit includes: 1 sliding door track 1 adjustable floor guide 4 dial-adjust door hangers 2 brass plated finger pulls Necessary fasteners

IMPORTANT INFORMATION

Pictures provided for visual reference only: actual product may vary. All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. Always remove debris/dust/residue (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. Never spray lubricant.



DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS























