



Commercial Hinge Pin Door Stop Saver

Product # 221301286

DESCRIPTION

DoorSaver II is simple to install, looks great, and stays in place without 'creeping up.' Its ultra low profile design replaces the hinge pin to create bumperless protection for doors and trim.

Works with commercial hinges 3-1/2 in and 4 in high with 0.31 in diameter pin.

- Bumperless design eliminates damage to doors and trim: the door stop does not come in contact with the door or door casing
- Ultra low profile
- Installs in seconds
- Hinge-mounted to fit all commercial doors
- Won't 'creep up' like conventional hinge-mounted products (on hinges 3-1/2" and 4" high with 0.31" diameter pin)
- Has multiple adjustments to create the perfect stopping point
- The stopping point can be readjusted quickly and easily
- Made from strong carbon steel

TECHNICAL SPECIFICATIONS

Product #	221301286
Diameter	0.31
Material	Metal
Brand	Onward
Color/Finish	Oil-Rubbed Bronze
Handing Position / Opening Side	Not Handed
Function	Door Stop
Usage	Hinge Door, Commercial Door
Collection	Door Hardware
Collection	Door Stops, Door Hardware



PRODUCT PHOTOS









INSTRUCTION INSTRUCTIONS
INSTRUCTION POUR INSTRUCTIONS
INSTRUCTION POUR INSTRUCTIONS
INSTRUCTION POUR INSTRUCTIONS
INSTRUCTION POUR INSTRUCTIONS
INSTRUCTIONS PARA INSTALAR







MADE IN CHINA

FABRIQUÉ EN CHINE

- Remove old hinge pin.
 Retirer le vieux pivot epingie.
 Renueva la espiga de bisagra vieja.

 2. Drop in the DoorSaver II Commercial.
 Laisser tomber la DoorSaver II Commercial.
 Laisser tomber la DoorSaver II Commercial en la bisagra

 3. Adjust to pau mutil door opens to desired
 angle. (Rotating top cam, as in figure 80,
 provides additional settings.) Install optional
 screw cap:
 Adjuster le haut cam j'usque la porte s'ouvre
 a' langle desirer. (Rotation le haut cam comme
 dans l'inage 38, Genonta dation monture)
 Installer facultatif boulon a vis:
 Ajuste la leva superior hasta que la puerta se