



## Round Rail Hanger with Ball Bearings and Flexible Long Offset Threaded Mounting Pin

**Product #** 24651078XB

### DESCRIPTION

**8 in offset bolt is threaded 5 1/2 in**

Designed for round rail sliding doors. Easy to install. Features a slick, smooth slide upon rail.

### ADVANTAGES AND BENEFITS

Easy to install

## REQUIRED PRODUCTS

Requires the following products



**Heavy-Duty Round Rail**

## TECHNICAL SPECIFICATIONS

<b>Product #</b>	24651078XB
<b>Product type</b>	Trolley, Track, Round Track
<b>Door Material</b>	Aluminum/Metal Frame, Wood
<b>Door Position</b>	In Front of Wall
<b>Roller Position</b>	Upper
<b>Door Thickness</b>	1 1/2 to 3 1/2 in
<b>Number of Doors</b>	1
<b>Roller Type</b>	Ball Bearing
<b>Overall Length</b>	7 53/64 in
<b>Finish</b>	Zinc Plated
<b>Load Capacity</b>	Max. 600 lb
<b>Width</b>	6 in
<b>Application</b>	Barn Door
<b>Overall Height</b>	1 3/4 in

---

## APPLICATION

Garages, sliding barn doors, industrial door tracks.

## IMPORTANT INFORMATION

Place hangers to distribute door weight evenly, keeping a minimum of 3 in from the door edges. If door panels are more than 16 ft wide, use 3 hangers per panel. Note: Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples of the assembly of different suppliers' hardware. The customer cannot base any claims on the use of these documents. No responsibility is assumed for design details relating to a particular construction project. At all times, execution and installation must be undertaken by qualified persons. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer. Always be sure to install the product correctly using the right fasteners for your materials. Never use any spray lubricant on these products.

## DISCLAIMER

The preceding information, as well as any technical recommendations given in writing, verbally or based on tests, is provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS

