



## **Heavy Duty Galvanized Steel Box Rail with Flashing**

**Product #** 24651090GABC

**Overall Length** 12 ft

**Packaging format** Length of 12 linear foot

### **DESCRIPTION**

Commercial trolley track with flashing for sliding doors on heavy-duty industrial garage and barn doors. Generally used for exterior doors and purposes. Simple installation.

### **ADVANTAGES AND BENEFITS**

No brackets required as the flashing provides continuous bracket support and prevents the accumulation of snow and ice.

## REQUIRED PRODUCTS

Requires ONE of the following products

Sales unit



**Dual Axis Box Rail Hanger with Ball Bearings and Apron Mounting Hinge**  
Product # 24651411XV

Bag

OR



**Flexible Dual Axis Box Rail Hanger with Bushing Rollers and Long, Threaded Flexible, Offset Mounting Pin**  
Product # 24651077XB

Pair

OR



**Dual Axis Box Rail Hanger with Fixed Mounting Apron**  
Product # 24654112XV

Bag


OR



**Dual Axis Box Rail Hanger with Ball Bearings and Fixed Mounting Apron**  
Product # 24651388XV

Bag

OR



**Single Axis Box Rail Hanger with Ball Bearings and Short Threaded Mounting Pin**  
Product # 24651385XV

Bag

OR



**Double Axle Box Rail Hangers with Ball Bearings and Short-Threaded Fixed Mounting Pin**  
Product # 24651384XV

Bag

OR



**Dual Axis Box Rail Hangers with Bushing rollers and Fixed Short Threaded Mounting Pin**  
Product # 24651383XV

Bag

## TECHNICAL SPECIFICATIONS

Product #	24651090GABC
Product type	Track, Box Track
Door Material	Aluminum/Metal Frame, Wood
Door Position	In Front of Wall
Track Mounting	Wall Mount
Door Thickness	1 1/2 to 3 1/2 in
Track type	Running
Width	1 7/8 in
Load Capacity	Max. 450 lb
Finish	Galvanized
Overall Height	2 3/8 in

## APPLICATION

Garage, sliding barn, industrial doors.

## IMPORTANT INFORMATION

For doors weighing up to 450 lbs per panel. Note: Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples of the assembly of different suppliers' hardware. The customer cannot base any claims on the use of these documents. No responsibility is assumed for design details relating to a particular construction project. At all times, execution and installation must be undertaken by qualified persons. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer. Always be sure to install the product correctly using the right fasteners for your materials. Never use any spray lubricant on these products.

## DISCLAIMER

The preceding information, as well as any technical recommendations given in writing, verbally or based on tests, is provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

