



Adjustable Stay Roller for Sliding Door

Product # 24651394XV

DESCRIPTION

Durable manufacturing provides greater bracing and holding strength than the traditional single-support. Features an adjustable roller to meet your needs. Easy to install.

ADVANTAGES AND BENEFITS

Easy to install, roller is adjustable

TECHNICAL SPECIFICATIONS

Product #	24651394XV
Product type	Accessories
Door Material	Aluminum/Metal Frame, Wood
Door Thickness	1 1/2 to 3 3/4 in
Overall Length	5 1/2 in
Width	3 15/16 in
Groove Needed for Guiding System	No
Finish	Zinc Plated
Screw/Nail Included	Yes
Manufacturing Material	Steel, Plastic
Application	Barn Door
Overall Height	4 in

IMPORTANT INFORMATION

Note: Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples of the assembly of different suppliers' hardware. The customer cannot base any claims on the use of these documents. No responsibility is assumed for design details relating to a particular construction project. At all times, execution and installation must be undertaken by qualified persons. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer. Always be sure to install the product correctly using the right fasteners for your materials. Never use any spray lubricant on these products.

APPLICATION

Roller for sliding door

INCLUDED PRODUCT(S)

Screws

DISCLAIMER

The preceding information, as well as any technical recommendations given in writing, verbally or based on tests, is provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

