



KT Drop-Down Door Seal

Product # 31096B

DESCRIPTION

- Seal height up to 18 mm
- With optimal sealing, sound insulation value up to 48 dB
- Protected silicone lip because it is deeper embedded
- Unilateral and noiseless release
- Thanks to the parallel lowering, there is no dragging across the floor
- Automatic compensation for sloping floors
- One groove size for all requirements
- For double-leaf doors with square or drive bolts
- High quality silicone lip, easy stroke adjustment
- Can be shortened to the next shorter storage length
- 7-year guarantee

ADVANTAGES AND BENEFITS

- Smoke-proof - Fire-retardant - Sound-insulating - 7-year guarantee

TECHNICAL SPECIFICATIONS

Product #	31096B
Color/Finish	Aluminum
Door Type	Wood, Metal, PVC
Standards and Certifications	cULus, UL R38125
Screw	Included
Height	31/32 in*
Width	1/2 in*
Length	37 3/4 in*
Material	Aluminum
Brand	Planet
Usage	Hinge Door
Handing Position / Opening Side	Not Handed

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

APPLICATION

- For hinged doors - For wood doors - Can also be used with metal and PVC doors



PRODUCT PHOTOS





