



Euro Series Industrial Rubber Casters

Product # F24802

Load Capacity Per Caster Max. 154 lb*

Wheel Diameter 3 15/16 in*

Total Height 5 1/32 in*

Tread Width 1 3/16 in*

Fastening Type Swivel with Double-Lock Brake

Axle Diameter 15/32 in*

Axle Length 1 9/16 in*

Mounting Hole Diameter 11/32 in*

Mounting Plate Dimensions 3 5/32 in x 4 1/32 in (80 mm x 102 mm)

DESCRIPTION

Superior rolling quality

These Euro series industrial rubber casters are suitable for surfaces that have water, detergent, petroleum, or by-products. Available with fixed, swivel, or double locking plate.

ADVANTAGES AND BENEFITS

- Metal thread guard - Double-lock braking system for both the wheel and the swivel (F24801, F24802, and F24803) - Grease seal holds in lubricant - Corrosion-resistant zinc finish - Fully seated ball bearing eliminates the need for axle lubrication, thus reducing maintenance costs - Two independent rows of hardened, polished precision ball bearings roll freely in large-diameter lubricated raceways

TECHNICAL SPECIFICATIONS

Product #	F24802
Mounting Type	Plate
Material	Euro Series Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt
Finish	Black
Conditions	Water, Detergent, Petroleum Products

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

