



## Industrial Pneumatic Casters

**Product #** F26488

**Load Capacity Per Caster** Max. 220 lb\*

**Wheel Diameter** 8 in\*

**Total Height** 10 in\*

**Tread Width** 2 1/2 in\*

**Fastening Type** Swivel Without Brake

### DESCRIPTION

#### Absorb shocks and vibrations

Industrial pneumatic casters. Absorbs shocks and vibration. Suitable for concrete, wood, asphalt, and gravel. Moves delicate loads smoothly and safely over rough surfaces.

### ADVANTAGES AND BENEFITS

- Designed to absorb shocks and vibrations caused by floor obstructions or outdoor terrain - Moves delicate loads smoothly and safely over rough surfaces

## TECHNICAL SPECIFICATIONS

<b>Product #</b>	F26488
<b>Mounting Type</b>	Plate
<b>Material</b>	Rubber
<b>Recommended Surfaces</b>	Concrete, Wood/Planking, Asphalt, Gravel
<b>Finish</b>	Black
<b>Axle Diameter</b>	5/8 in*
<b>Axle Length</b>	3 27/32 in*
<b>Mounting Hole Diameter</b>	13/32 in*
<b>Mounting Plate Dimensions</b>	3 15/16 in x 4 17/32 in (100 mm x 115 mm)
<b>Conditions</b>	Water
<b>Tread Type</b>	Sawtooth

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

## DISCLAIMER

Technical data subject to without prior notice.

## PRODUCT PHOTOS

