

3" Magnetic Door Stop


Color/Finish



Antique Brass




Antique Nickel



Brass


Brushed
Nickel


Chrome


Oil-Rubbed
Bronze

Packaging format

Blister

Bag

DESCRIPTION

Protects walls from swing of door and keeps door open

This magnetic door stop is used to protect your walls from the swing of the door thanks to its powerful magnets. In addition to preventing damage to walls and doors, this magnetic door stop also allows the door to remain open. Easy to install, and available in a variety of stylish finishes.

ADVANTAGES AND BENEFITS

Easy to install. Magnetism allows the door to remain open, with 5 lb of holding force. Prevents wall and door damages.

AVAILABLE PRODUCTS

Product #	Color/Finish	Packaging format
67ABR	Antique Brass	Blister
67ANR	Antique Nickel	Blister
67BR	Brass	Blister
67NBR	Brushed Nickel	Blister
67NBV	Brushed Nickel	Bag
67CR	Chrome	Blister
67ORBR	Oil-Rubbed Bronze	Blister

TECHNICAL SPECIFICATIONS

Type	Magnetic
Screw/Nail	Wood Screw (Included)
Base Diameter	1 3/4 in*
Tip Diameter	1 1/4 in*
Base Height	3 in*
Holding Force	5 lb
Screw	Included
Height	3 in*
Width	3 in*
Length	3 in
Projection	3 in
Material	Metal
Brand	Onward
Weight Capacity	0 lb
Function	Door Stop
Usage	Hinge Door
Collection	Door Hardware

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Installation: 1. Mark screw locations on wall and door. 2. Drill 3/32" pilot holes in wall and door. 3. Fasten doorstop as indicated. Use: To protect walls from door swinging and to keep door open.

INCLUDED PRODUCT(S)

Door stop with #6 x 3/4" wood screw.

PRODUCT PHOTOS

