



## 1600 Series Fixed Power Door Closer - Grade 2

### Force #

no. 2

no. 3

no. 4

### Weight Capacity

55.1 to 99.2 lb\*

88.2 to 143 lb\*

176 to 220 lb\*

### Body Type

N°1

N°2

N°3

N°4

### Grade

2

3

### Width

2.6562 in

2.8281 in

2.8437 in

### Length

7 in

7 in

7.4062 in

8.1875 in

9.0625 in

## DESCRIPTION

- Adjustable latching speed and closing speed
- Compatible with left-hand and right-hand doors
- Maximum 180° opening angle
- Tri-pack for regular, parallel arm and top jamb installation
- Precision cast aluminum alloy housing
- Rack and pinion mechanism
- Non-critical thermostatic valves
- High quality non-gumming and non-freezing hydraulic fluid
- CUL and UL listed
- 5 year limited warranty on finishes

## AVAILABLE PRODUCTS

Product #	Force #	Weight Capacity	Body Type	Grade	Width	Length
<b>1600SI21BC</b>	no. 2	55.1 to 99.2 lb*	N°1	3	2.6562 in	7 in
<b>1600SI22BC</b>	no. 2	55.1 to 99.2 lb*	N°2	2	2.8437 in	7 in
<b>1600SI32BC</b>	no. 3	88.2 to 143 lb*	N°2	2	2.8437 in	7.4062 in
<b>1600SI33BC</b>	no. 3	88.2 to 143 lb*	N°3	2	2.8437 in	8.1875 in
<b>1600SI44BC</b>	no. 4	176 to 220 lb*	N°4	2	2.8281 in	9.0625 in

## TECHNICAL SPECIFICATIONS

Characteristic	Non Hold-Open
Color/Finish	Satin Aluminum
Usage	Hinge Door
Guarantee	5-year guarantee
Collection	Door Closers
Standards and Certifications	UL10C, ANSI A156.4
Projection	2 27/32 in*
Material	Aluminum
Handing Position / Opening Side	Reversible for Left or Right
Screw/Nail	Included

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## INCLUDED PRODUCT(S)

Mounting hardware included.

## PRODUCT PHOTOS

