



Industrial Gray Thermoplastic Rubber Caster

Load Capacity Per Caster

Max. 247 lb*

Max. 298 lb*

Wheel Diameter

4 1/32 in*

5 in*

Total Height

4 31/32 in*

6 5/32 in*

Fastening Type



Fixed


Swivel with
Brake

Swivel
Without Brake

Mounting Plate Dimensions

2 29/32 in x 4
1/8 in (74 mm
x 105 mm)

2 7/8 in x 3
5/8 in (73 mm
x 92 mm)

DESCRIPTION

Non-marking rubber tread

These heavy-duty casters are durable and designed for use in the most demanding environments. Available in three heights. Fixed or swivel design, with or without brakes.

ADVANTAGES AND BENEFITS

- Non-marking rubber tread - Polypropylene rim resistant to nicks, scratches, stains, and deterioration
- Thermoplastic rubber resistant to chemicals, caustics, oils, and wear
- Corrosion-resistant zinc finish

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Fastening Type	Mounting Plate Dimensions
F27275	Max. 247 lb*	4 1/32 in*	4 31/32 in*	Fixed	2 29/32 in x 4 1/8 in (74 mm x 105 mm)
F25622	Max. 247 lb*	4 1/32 in*	4 31/32 in*	Swivel with Brake	2 7/8 in x 3 5/8 in (73 mm x 92 mm)
F25656	Max. 247 lb*	4 1/32 in*	4 31/32 in*	Swivel Without Brake	2 7/8 in x 3 5/8 in (73 mm x 92 mm)
F25657	Max. 298 lb*	5 in*	6 5/32 in*	Swivel Without Brake	2 7/8 in x 3 5/8 in (73 mm x 92 mm)

TECHNICAL SPECIFICATIONS

Tread Width	1 1/4 in*
Mounting Type	Plate
Material	TPR (Thermoplastic Rubber)
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate
Finish	Gray
Conditions	Water, Solvents, Detergent, Acids, Extreme Cold, Petroleum Products

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

