



Industrial Blue Elastic Rubber Caster

Load Capacity Per Caster

Max. 331 lb*

Max. 397 lb*

Wheel Diameter

3 15/16 in*

4 29/32 in*

Total Height

5 1/32 in*

6 3/32 in*

Tread Width

1 3/8 in*

1 9/16 in*

Fastening Type



Fixed


Swivel with
Double-Lock
Brake

Swivel
Without Brake

Axle Diameter

15/32 in*

19/32 in*

Axle Length

1 9/16 in*

1 13/16 in*

Mounting Plate Dimensions

3 11/32 in x 4
3/32 in (85
mm x 104
mm)

3 5/32 in x 4
1/8 in (80 mm
x 105 mm)

3 7/16 in x 4
in (87 mm x
102 mm)

DESCRIPTION

Non-marking rubber tread

Blue non-marking runner tread. These heavy-duty casters are durable and designed for use in the most demanding environments. Available in fixed or swivel design, with several braking options.

ADVANTAGES AND BENEFITS

- Double-lock braking system for both the wheel and the swivel (F08336, F08339, and F24800) - Non-marking rubber tread - Low starting effort, rolls easily; tread does not flat-spot - Metal thread guards - Grease seal to hold in lubricant - Corrosion-resistant zinc finish

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Axle Diameter	Axle Length	Mounting Plate Dimensions
F08334	Max. 331 lb*	3 15/16 in*	5 1/32 in*	1 3/8 in*	Fixed	15/32 in*	1 9/16 in*	3 7/16 in x 4 in (87 mm x 102 mm)
F08336	Max. 331 lb*	3 15/16 in*	5 1/32 in*	1 3/8 in*	Swivel with Double-Lock Brake	15/32 in*	1 9/16 in*	3 5/32 in x 4 1/8 in (80 mm x 105 mm)
F08335	Max. 331 lb*	3 15/16 in*	5 1/32 in*	1 3/8 in*	Swivel Without Brake	15/32 in*	1 9/16 in*	3 5/32 in x 4 1/8 in (80 mm x 105 mm)
F08337	Max. 397 lb*	4 29/32 in*	6 3/32 in*	1 9/16 in*	Fixed	19/32 in*	1 13/16 in*	3 11/32 in x 4 3/32 in (85 mm x 104 mm)
F08339	Max. 397 lb*	4 29/32 in*	6 3/32 in*	1 9/16 in*	Swivel with Double-Lock Brake	19/32 in*	1 13/16 in*	3 5/32 in x 4 1/8 in (80 mm x 105 mm)
F08338	Max. 397 lb*	4 29/32 in*	6 3/32 in*	1 9/16 in*	Swivel Without Brake	19/32 in*	1 13/16 in*	3 5/32 in x 4 1/8 in (80 mm x 105 mm)

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	Elastic Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate
Finish	Blue
Mounting Hole Diameter	11/32 in*
Conditions	Water, Solvents, Detergent, Extreme Cold, Extreme Heat, Petroleum Products

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

