



Industrial Black General-Duty Rubber Casters

Load Capacity Per Caster

Max. 33.1 lb*	Max. 44.1 lb*	Max. 126 lb*	Max. 176 lb*	Max. 209 lb*
Max. 247 lb*	Max. 298 lb*			

Wheel Diameter

1 3/16 in*	1 9/16 in*	1 31/32 in*	2 15/32 in*	2 15/16 in*
4 1/32 in*	4 29/32 in*			




Total Height

1 1/2 in*	1 21/32 in*	2 in*	2 1/16 in*	2 7/16 in*
3 7/32 in*	3 13/16 in*	5 in*	6 1/8 in*	

Tread Width

1/2 in*	9/16 in*	21/32 in*	29/32 in*	1 1/16 in*
1 1/4 in*	1 1/4 in*	1 9/32 in*		

Fastening Type

		
Fixed	Swivel with Brake	Swivel Without Brake

Axle Diameter

1/16 in*	1/4 in*	5/16 in*	11/32 in*	13/32 in*
----------	---------	----------	-----------	-----------

Axle Length

31/32 in*	1 5/16 in*	1 11/32 in*	1 17/32 in*	1 9/16 in*
-----------	------------	-------------	-------------	------------

Mounting Hole Diameter

5/32 in*	3/16 in*	7/32 in*	1/4 in*	9/32 in*
5/16 in*	11/32 in*	11/32 in*	13/32 in*	

Mounting Plate Dimensions

1 1/2 in x 2 11/16 in (38 mm x 68 mm)	1 17/32 in x 1 27/32 in (39 mm x 47 mm)	1 29/32 in x 2 9/16 in (48 mm x 65 mm)	1 9/32 in x 1 1/2 in (32 mm x 38 mm)	2 17/32 in x 3 21/32 in (64 mm x 93 mm)
2 3/8 in x 3 5/8 in (60 mm x 92 mm)	25/32 in x 1 15/32 in (20 mm x 37 mm)	2 7/16 in x 4 7/8 in (62 mm x 124 mm)	2 7/32 in x 4 15/32 in (56 mm x 113 mm)	31/32 in x 1 13/16 in (25 mm x 46 mm)
				3 1/8 in x 4 1/8 in (79.5 mm x 105 mm)
3 7/8 in x 2 3/4 in (98 mm x 70 mm)				

DESCRIPTION

Combines strength and durability

These industrial black general-duty rubber casters are suitable for surfaces that have water, petroleum, or by-products. Available in seven different heights.

ADVANTAGES AND BENEFITS

- Combines strength and durability - Soft rubber tread combined with hard rubber rim for motion stability

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Axle Diameter	Axle Length	Mounting Hole Diameter	Mounting Plate Dimensions
F22902	Max. 33.1 lb*	1 3/16 in*	1 1/2 in*	9/16 in*	Fixed	1/16 in*	1 5/16 in*	5/32 in*	25/32 in x 1 15/32 in (20 mm x 37 mm)
F22900	Max. 33.1 lb*	1 3/16 in*	1 21/32 in*	1/2 in*	Swivel Without Brake	1/16 in*	1 5/16 in*	5/32 in*	1 9/32 in x 1 1/2 in (32 mm x 38 mm)
F22903	Max. 44.1 lb*	1 9/16 in*	2 in*	21/32 in*	Fixed	1/16 in*	1 17/32 in*	7/32 in*	31/32 in x 1 13/16 in (25 mm x 46 mm)
F22901	Max. 44.1 lb*	1 9/16 in*	2 1/16 in*	21/32 in*	Swivel Without Brake	1/16 in*	1 17/32 in*	3/16 in*	1 17/32 in x 1 27/32 in (39 mm x 47 mm)
F25748	Max. 126 lb*	1 31/32 in*	2 7/16 in*	29/32 in*	Fixed	1/4 in*	31/32 in*	9/32 in*	1 1/2 in x 2 11/16 in (38 mm x 68 mm)
F25086	Max. 126 lb*	1 31/32 in*	2 7/16 in*	29/32 in*	Swivel with Brake	1/4 in*	31/32 in*	1/4 in*	1 29/32 in x 2 9/16 in (48 mm x 65 mm)
F25082	Max. 126 lb*	1 31/32 in*	2 7/16 in*	29/32 in*	Swivel Without Brake	1/4 in*	31/32 in*	1/4 in*	1 29/32 in x 2 9/16 in (48 mm x 65 mm)
F25749	Max. 176 lb*	2 15/32 in*	3 7/32 in*	1 1/16 in*	Fixed	5/16 in*	1 11/32 in*	11/32 in*	2 7/32 in x 4 15/32 in (56 mm x 113 mm)
F25160	Max. 176 lb*	2 15/32 in*	3 7/32 in*	1 1/16 in*	Swivel with Brake	5/16 in*	1 11/32 in*	5/16 in*	3 7/8 in x 2 3/4 in (98 mm x 70 mm)
F25083	Max. 176 lb*	2 15/32 in*	3 7/32 in*	1 1/16 in*	Swivel Without Brake	5/16 in*	1 11/32 in*	5/16 in*	3 7/8 in x 2 3/4 in (98 mm x 70 mm)
F25752	Max. 209 lb*	2 15/16 in*	3 13/16 in*	1 9/32 in*	Fixed	11/32 in*	1 9/16 in*	11/32 in*	2 7/16 in x 4 7/8 in (62 mm x 124 mm)
F25095	Max. 209 lb*	2 15/16 in*	3 13/16 in*	1 9/32 in*	Swivel with Brake	13/32 in*	1 9/16 in*	11/32 in*	3 1/8 in x 4 1/8 in (79.5 mm x 105 mm)
F25091	Max. 209 lb*	2 15/16 in*	3 13/16 in*	1 9/32 in*	Swivel Without Brake	13/32 in*	1 9/16 in*	11/32 in*	3 1/8 in x 4 1/8 in (79.5 mm x 105 mm)
F27280	Max. 247 lb*	4 1/32 in*	5 in*	1 1/4 in*	Fixed	13/32 in*	1 17/32 in*	11/32 in*	2 3/8 in x 3 5/8 in (60 mm x 92 mm)
F25415	Max. 247 lb*	4 1/32 in*	5 in*	1 1/4 in*	Swivel with Brake	13/32 in*	1 17/32 in*	13/32 in*	2 17/32 in x 3 21/32 in (64 mm x 93 mm)
F25413	Max. 247 lb*	4 1/32 in*	5 in*	1 1/4 in*	Swivel Without Brake	13/32 in*	1 17/32 in*	13/32 in*	2 17/32 in x 3 21/32 in (64 mm x 93 mm)
F27281	Max. 298 lb*	4 29/32 in*	6 1/8 in*	1 1/4 in*	Fixed	13/32 in*	1 9/16 in*	11/32 in*	2 3/8 in x 3 5/8 in (60 mm x 92 mm)
F25533	Max. 298 lb*	4 29/32 in*	6 1/8 in*	1 1/4 in*	Swivel Without Brake	13/32 in*	1 9/16 in*	11/32 in*	2 3/8 in x 3 5/8 in (60 mm x 92 mm)

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	General Duty Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt
Finish	Black
Conditions	Water, Detergent, Petroleum Products

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

