



Euro Series Industrial Rubber Casters

Load Capacity Per Caster

Max. 110 lb*

Max. 154 lb*

Max. 220 lb*

Max. 309 lb*

Wheel Diameter

3 5/32 in*

3 15/16 in*

4 29/32 in*

6 5/16 in*

Total Height

4 1/8 in*

5 1/32 in*

6 3/32 in*

7 11/16 in*

Tread Width

31/32 in*

1 3/16 in*

1 15/32 in*

1 9/16 in*

Fastening Type



Fixed


Swivel with
Double-Lock
Brake

Swivel
Without Brake

Axle Diameter

15/32 in*

19/32 in*

25/32 in*

Axle Length

1 9/16 in*

1 15/16 in*

2 5/16 in*

Mounting Hole Diameter

11/32 in*

15/32 in*

Mounting Plate Dimensions

3 5/32 in x 4
1/32 in (80
mm x 102
mm)

4 11/32 in x 5
5/16 in (110
mm x 135
mm)

DESCRIPTION

Superior rolling quality

These Euro series industrial rubber casters are suitable for surfaces that have water, detergent, petroleum, or by-products. Available with fixed, swivel, or double locking plate.

ADVANTAGES AND BENEFITS

- Metal thread guard - Double-lock braking system for both the wheel and the swivel (F24801, F24802, and F24803) - Grease seal holds in lubricant - Corrosion-resistant zinc finish - Fully seated ball bearing eliminates the need for axle lubrication, thus reducing maintenance costs - Two independent rows of hardened, polished precision ball bearings roll freely in large-diameter lubricated raceways

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Axle Diameter	Axle Length	Mounting Hole Diameter	Mounting Plate Dimensions
F24796	Max. 110 lb*	3 5/32 in*	4 1/8 in*	31/32 in*	Fixed	15/32 in*	1 9/16 in*	11/32 in*	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24790	Max. 110 lb*	3 5/32 in*	4 1/8 in*	31/32 in*	Swivel Without Brake	15/32 in*	1 9/16 in*	11/32 in*	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24797	Max. 154 lb*	3 15/16 in*	5 1/32 in*	1 3/16 in*	Fixed	15/32 in*	1 9/16 in*	11/32 in*	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24802	Max. 154 lb*	3 15/16 in*	5 1/32 in*	1 3/16 in*	Swivel with Double-Lock Brake	15/32 in*	1 9/16 in*	11/32 in*	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24791	Max. 154 lb*	3 15/16 in*	5 1/32 in*	1 3/16 in*	Swivel Without Brake	15/32 in*	1 9/16 in*	11/32 in*	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24798	Max. 220 lb*	4 29/32 in*	6 3/32 in*	1 15/32 in*	Fixed	19/32 in*	1 15/16 in*	11/32 in*	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24792	Max. 220 lb*	4 29/32 in*	6 3/32 in*	1 15/32 in*	Swivel Without Brake	19/32 in*	1 15/16 in*	11/32 in*	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24788	Max. 309 lb*	6 5/16 in*	7 11/16 in*	1 9/16 in*	Swivel Without Brake	25/32 in*	2 5/16 in*	15/32 in*	4 11/32 in x 5 5/16 in (110 mm x 135 mm)

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	Euro Series Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt
Finish	Black
Conditions	Water, Detergent, Petroleum Products

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

