



Industrial Pneumatic Casters

Load Capacity Per Caster

Max. 220 lb*

Max. 265 lb*

Wheel Diameter

8 in*

10 in*

Total Height

10 in*

11 3/4 in*

Tread Width

2 1/2 in*

3 1/2 in*

Fastening Type



Fixed


Swivel
Without Brake

DESCRIPTION

Absorb shocks and vibrations

Industrial pneumatic casters. Absorbs shocks and vibration. Suitable for concrete, wood, asphalt, and gravel. Moves delicate loads smoothly and safely over rough surfaces.

ADVANTAGES AND BENEFITS

- Designed to absorb shocks and vibrations caused by floor obstructions or outdoor terrain - Moves delicate loads smoothly and safely over rough surfaces

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type
F27458	Max. 220 lb*	8 in*	10 in*	2 1/2 in*	Fixed
F26488	Max. 220 lb*	8 in*	10 in*	2 1/2 in*	Swivel Without Brake
F27358	Max. 265 lb*	10 in*	11 3/4 in*	3 1/2 in*	Fixed

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	Rubber
Recommended Surfaces	Concrete, Wood/Planking, Asphalt, Gravel
Finish	Black
Axle Diameter	5/8 in*
Axle Length	3 27/32 in*
Mounting Hole Diameter	13/32 in*
Mounting Plate Dimensions	3 15/16 in x 4 17/32 in (100 mm x 115 mm)
Conditions	Water
Tread Type	Sawtooth

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to without prior notice.

PRODUCT PHOTOS

