



## Vertical Rod Panic Bars - 536/548 Series

### Door Width Requirements

30 to 36 in

36 to 48 in

### Required Door Height

Max. 7 ft

Max. 8 ft

### Handing Position / Opening Side

Left-Hand  
Opening

Right-Hand  
Opening

### Length

36 in

48 in

## DESCRIPTION

Designed for heavy-duty applications, our 536/548 series panic bars are built to ANSI Grade 1 standards. Available in left-hand and right-hand configurations.

## ADVANTAGES AND BENEFITS

- Cylinders: 6-pin standard where applicable - Material: push bar in extruded anodized aluminum, spring in stainless steel - Latchbolts: stainless steel - Deadbolts: stainless steel - Finish: push bar anodized, cover painted

## AVAILABLE PRODUCTS

Product #	Door Width Requirements	Required Door Height	Handing Position / Opening Side	Length
<b>536EVLAL</b>	30 to 36 in	Max. 7 ft	Left-Hand Opening	36 in
<b>536EVRAL</b>	30 to 36 in	Max. 7 ft	Right-Hand Opening	36 in
<b>548EVLAL</b>	36 to 48 in	Max. 8 ft	Left-Hand Opening	48 in
<b>548EVRAL</b>	36 to 48 in	Max. 8 ft	Right-Hand Opening	48 in

## TECHNICAL SPECIFICATIONS

<b>Dogging</b>	Standard 1/4 Turn Allen Type
<b>Projection Pushpad Depressed</b>	1 7/8 in
<b>Projection Pushpad Neutral</b>	2 1/2 in
<b>Top Latch</b>	3/4 in
<b>Bottom Latch</b>	3/4 in
<b>Backset</b>	2 3/4 in
<b>Minimum Frame Width</b>	3 1/2 in
<b>Strike</b>	5/8 in
<b>Standards and Certifications</b>	ANSI BHMA A156.3
<b>Color/Finish</b>	Satin Aluminum
<b>Door Thickness</b>	1 3/4 in
<b>Grade</b>	1
<b>Fire-Rating</b>	Not Certified
<b>Mounting Hardware</b>	Included
<b>Mounting Height</b>	40 5/16 in
<b>Latchbolt Throw</b>	3/4 in
<b>Deadbolt Throw</b>	1/2 in
<b>Strike</b>	1/2 to 5/8 in
<b>Finish Warranty</b>	5 Years
<b>Mechanical Warranty</b>	10 Years

## PRODUCT PHOTOS

---

