



Rim Type Panic Bars (Fire-Rated) - 536/548 Series

Door Width Requirements

30 to 36 in

36 to 48 in

Length

36 in

48 in

DESCRIPTION

Designed for heavy-duty applications, our 536/548 series panic bars are built to ANSI Grade 1 standards and fire-rated for up to 3 hours.

ADVANTAGES AND BENEFITS

- Cylinders: 6-pin standard where applicable - Material: push bar in extruded anodized aluminum, spring in stainless steel - Latchbolts: stainless steel - Deadbolts: stainless steel - Finish: push bar anodized, cover painted

AVAILABLE PRODUCTS

Product #	Door Width Requirements	Length
536EFRAL	30 to 36 in	36 in
548EFRAL	36 to 48 in	48 in

TECHNICAL SPECIFICATIONS

Minimum Frame Width	4 1/2 in
Grade	1
Standards and Certifications	UL10C, UBC 7-2-1997, ANSI BHMA A156.3
Fire-Rating	3 hours
Door Thickness	1 3/4 in
Backset	2 3/4 in
Projection Pushpad Depressed	1 7/8 in
Projection Pushpad Neutral	2 1/2 in
Color/Finish	Satin Aluminum
Handing Position / Opening Side	Reversible for Left or Right
Mounting Hardware	Included
Retaining	Not an Option
Mounting Height	40 5/16 in
Dogging	1/4 in
Latchbolt Throw	3/4 in
Deadbolt Throw	1/2 in
Strike	1/2 to 5/8 in
Finish Warranty	5 Years
Mechanical Warranty	10 Years

PRODUCT PHOTOS

