



## RH Drop-Down Door Seal

### Handing Position / Opening Side

Left-Hand  
Opening

Right-Hand  
Opening

### DESCRIPTION

- Seal height up to 27 mm
- With optimal sealing, sound insulation value up to 44 dB
- For wavy, humped, hollow, sloping, and uneven floors
- Soft silicone bevel lip seal
- Inclined compensation for 1000 mm door width: 15 mm
- Unilateral and noiseless release, whisper seal
- Thanks to the parallel lowering, there is no dragging across the floor
- For double-leaf doors with square or drive bolts
- High quality silicone lip, easy stroke adjustment
- Can be shortened to the next shorter storage length
- No tedious silicone cutting on both ends
- 7-year guarantee

### ADVANTAGES AND BENEFITS

- Smoke-proof - Fire-retardant - Sound-insulating - 7-year guarantee

### AVAILABLE PRODUCTS

Product #	Handing Position / Opening Side
85096L	Left-Hand Opening
85096R	Right-Hand Opening

### TECHNICAL SPECIFICATIONS

Door Type	Wood, Metal, PVC
Standards and Certifications	cULus, UL R38125
Height	1 3/16 in*
Width	1/2 in*
Length	37 3/4 in*
Material	Aluminum
Brand	Planet
Usage	Hinge Door

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

### APPLICATION

- For hinged doors - For wood doors - Can also be used with metal and PVC doors

PRODUCT PHOTOS

